



ISSN: 2395-7852



International Journal of Advanced Research in Arts, Science, Engineering & Management

Volume 10, Issue 3, May 2023



INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 6.551

+91 9940572462

+91 9940572462

ijarasem@gmail.com

www.ijarasem.com

A Review Article on “Investigating Studies on Natural Fibrous Materials as Fixed Aerated Beds for Domestic Wastewater Treatment”

Rajat Meshram¹, Prof. Akash Gupta², Mr. Rajesh Ingole³

¹PG Student, Civil Engineering Department, Swaminarayan Siddhanta Institute Of Technology, Nagpur, Maharashtra, India

^{2,3}Assistant Professor, Civil Engineering Department, Swaminarayan Siddhanta Institute Of Technology, Nagpur, Maharashtra, India

Abstract-Water is one of the most important elements involved in the creation and development of healthy life. Since water is such a vital resource for survival of both plants and animals, it is our responsibility to manage this resource. Current and future fresh water demand could be met by enhancing water use efficiency and demand management. Thus wastewater or low quality water is emerging as potential source for demand management after essential treatment. The use of various fixed beds having higher surface area is effective in removing organic matter and nutrients from municipal wastewater. In present study efforts have been made to check the efficiency of two different fibrous material- Agave sisalana fibres and Areca husk fibres at two different packing densities and two different heights as submerged aerated fixed film beds for treating domestic wastewater. The use of agricultural by products in wastewater treatment can necessarily reduce the cost of treatment plant.

Keywords-Wastewater Treatment, Fixed aerated beds, Natural fibrous materials, Agave sisalana fibres, Areca husk fibres

I. INTRODUCTION

Water is considered as the most important and priceless commodity on planet Earth. Water on earth moves continually through the water cycle of evaporation and transpiration, condensation, precipitation and runoff, usually reaching the sea. It is one of the most essential thing that is required for every living being. In order to develop a healthy and hygienic environment, water quality should be monitored such that it lies within the respective standards. Wastewater is liquid waste discharged by domestic residences, commercial properties, industry, agriculture, which often contains some contaminants that result from the mixing of wastewater from different sources. Wastewater obtained from various sources need to be treated very effectively in order to create a hygienic environment. If proper arrangements for collection, treatment and disposal of all the waste produce from city or town are not made, they will go on accumulating and create a foul condition that the safety of the structures such that building, roads will be damaged due to accumulation of wastewater in the foundations. In addition to this, disease causing bacteria will breed up in the stagnant water and the health of the public will be in danger. The principal aim of wastewater treatment is generally to allow human and industrial effluents to be disposed of without danger to human health or unacceptable damage to the natural environment. Therefore in the interest of the community of the town or city it is most essential to collect, treat and dispose of all the wastewater of the city in such a way that it may not cause harm to the people residing in the town. The extent and the type of treatment required, however depends on the character and quality of both sewage and sources of disposal available.

The sewage after treatment may be disposed either into a water body such as lakes, streams, river, estuary and ocean or into land. It may be used for several purposes such as conservation, industrial use or reclaimed sewage effluent in cooling systems, boiler feed, process water, reuse in agriculture, horticulture, sericulture, reuse is becoming increasingly popular, especially in geographies where potable water is in short supply.

Reduction of strength of domestic wastewater using two different bed materials Areca Husk fibre and Agava sisalana fibre as a filter media is one such type of treatment method adopted. The utilization of fixed films for wastewater treatment process has been increasingly considered due to inherent advantages over suspended growth system. The present work is intended to study the application of the comparative study between the fibres ie., Areca fibre and Agava



sisalana as a fixed bed for treating domestic wastewater and to know the comparative removal efficiency of COD, BOD, nitrate, sulphate, chloride with conventional gravel bed in a small volume reactor.

The principal aim of wastewater treatment is generally to allow human and industrial effluents to be disposed of without danger to human health or unacceptable damage to the natural environment. Therefore in the interest of the community of the town or city it is most essential to collect, treat and dispose of all the wastewater of the city in such a way that it may not cause harm to the people residing in the town. The extent and the type of treatment required, however depends on the character and quality of both sewage and sources of disposal available.

Natural Fibre:

Natural fibres can be defined as bio-based fibres or fibres from vegetable and animal origin. This definition includes all natural cellulosic fibres (cotton, jute, sisal, coir, flax, hemp, abaca, ramie, etc.) and protein based fibres such as wool and silk. Excluded here are mineral fibres such as asbestos that occur naturally but are not bio based. Asbestos containing products are not considered sustainable due to the well known health risk, that resulted in prohibition of its use in many countries. On the other hand there are manmade cellulose fibres (e.g. viscose-rayon and cellulose acetate) that are produced with chemical procedures from pulped wood or other sources (cotton, bamboo). Similarly, regenerated (soybean) protein, polymer fibre (bio-polyester, PHA, PLA) and chitosan fibre are examples of semi-synthetic products that are based on renewable resources.

Objective and scope of the project:

The main objective of the study aims at treating the domestic wastewater in a fixed film reactor filled with Agave sisalana fibres and Areca husk fibres.

The specific objectives are:

1. To study the performance of the Agave sisalana fibres and Areca husk fibres used as filter media at different contact periods.
2. To study the comparative removal efficiency of COD, BOD, sulphate, nitrate using Agave sisalana and Areca husk fibres.

II. LITERATURE REVIEW

Water is vital to the existence of all living organisms, but this valued resource is increasingly being threatened as human populations grow and demand more water of high quality for domestic purposes and economic activities. Among the various environmental challenges of that India is facing this century, fresh water scarcity ranks very high. The key challenges to better management of the water quality in India are temporal and spatial variation of rainfall, improper management of surface runoff, uneven geographic distribution of surface water resources, persistent droughts, overuse of groundwater, and contamination, drainage, and salinization and water quality problems due to treated, partially treated, and untreated wastewater from urban settlements, industrial establishments, and run-off from the irrigation sector besides poor management of municipal solid waste and animal dung in rural areas.

Wastewater is any water that has been adversely affected in quality by anthropogenic influence. It comprises liquid waste discharged by domestic residences, commercial properties, industry, and/or agriculture and can encompass a wide range of potential contaminants and concentrations. In the most common usage, it refers to the municipal wastewater that contains a broad spectrum of contaminants resulting from the mixing of wastewaters from different sources. Wastewater also known as sewage originates from residential commercial and industrial area.

Wastewater engineering is that branch of environmental engineering in which the basic principles of science and engineering are applied to solving the issues associated with the treatment and reuse of wastewater. The ultimate goal of wastewater engineering is the protection of public health in a manner commensurate with environmental, economic, social, and political concerns. When untreated wastewater accumulates and is allowed to go septic, the decomposition of the organic matter it contains will lead to nuisance conditions including the production of malodorous gases. In addition, untreated wastewater contains numerous pathogenic microorganisms that dwell in the human intestinal tract. Wastewater also contains nutrients, which can stimulate the growth of aquatic plants, and may contain toxic compounds or compounds that potentially may be mutagenic or carcinogenic. For these reasons, the immediate and nuisance-free removal of wastewater from its sources of generation, followed by treatment, reuse, or dispersal into the environment is necessary to protect public health and the environment.

Besides that, the purpose of wastewater treatment is to remove pollutants that can harm the aquatic environment if they are discharged into it. Because of the deleterious effects of low dissolved oxygen concentrations on aquatic life, wastewater treatment engineers historically focused on the removal of pollutant that would deplete the DO in receiving

waters. Biological treatment is an important and integral part of any wastewater treatment plant that treats wastewater from either municipality or industry having soluble organic impurities or a mix of the two types of wastewater sources. The obvious economic advantage, both in terms of capital investment and operating costs, of biological treatment over other treatment processes like chemical oxidation; thermal oxidation etc. has cemented its place in any integrated wastewater treatment plant affected in quality by anthropogenic influence. It comprises liquid waste discharged by domestic residences, commercial properties, industry, and/or agriculture and can encompass a wide range of potential contaminants and concentrations. In the most common usage, it refers to the municipal wastewater that contains a broad spectrum of contaminants resulting from the mixing of wastewaters from different sources. Wastewater also known as sewage originates from residential commercial and industrial area. There are several opportunities for improving wastewater irrigation practices via improved policies, institutional dialogue, and financial mechanisms, which would reduce risks in agriculture. Effluent standards combined with incentives or enforcement can motivate improvements in water management by household and industrial sectors discharging wastewater from point sources. Segregation of chemical pollutants from urban wastewater facilitates treatment and reduces risk. Strengthening institutional capacity and establishing links between water delivery and sanitation sectors through inter-institutional coordination leads to more efficient management of wastewater and risk reduction.

India, being an economy in transition from a developing to a developed nation, faces two problems. On the one hand there is a lack of infrastructure and on the other, an ever-increasing urban population. The urban population in India has jumped from 25.8 million in 1901 to about 387 million (estimated) in 2011. This has thrown up two self-perpetuating problems, viz. Shortage of water and sewage overload. It is estimated that by 2050, more than 50 per cent of the country's population will live in cities and towns and thus the demand for infrastructure facilities is expected to rise sharply, posing a challenge to urban planners and policymakers. Public services have not been able to keep pace with rapid urbanization. Water supply, sanitation measures, and management of sewage and solid wastes cover only a fraction of the total urban population. There is clear inequity and disparity between the public services received by the inhabitants, depending on their economic strata. Slum dwellers have always received least attention from the civic authorities. The rapid growth of urban population has taken place due to huge migration of population (mostly from rural areas and small towns to big towns) and inclusion of newer rural areas in the nearest urban settings, apart from natural growth of urban population. The majority of towns and cities have no sewerage and sewage treatment services. Many cities have expanded beyond municipalities, but the new urban agglomerations remain under rural administrations, which do not have the capacity to handle the sewage. Management of sewage is worse in smaller towns. The sewage is either directly dumped into rivers or lakes or in open fields.

[1] Kudaligama et al., did a study on “Effect of Bio-brush medium: a coir fibre based biomass retained on treatment efficiency of an anaerobic filter type reactor”, which reveals that the efficiency of treatment increased with increase in SSA of the media and proper calibration of OLR in the reactor.

[2] Kevin M. Sherman et al., did a study on “Introducing a new media for fixed film treatment in Decentralised Wastewater systems”, which reveals that Quanics .Inc . has patented a product that combines advantages of both naturally and artificially occurring media. The product has successfully passed NSF Standard 40 certification.

[3] Vinod et al. , did a study on “Studies on natural fibrous material as submerged aerated beds for wastewater treatment”, which reveals that the maximum percentage reduction of COD(73%), BOD₅(80%), and Orthophosphate(82%) with increased retention time in both reactors. The used of natural fibrous materials as fixed bed in WWT shows promising removal efficiency of organic and nutrients.

[4] Padmini et al., Surface modified Agava sisalana as an adsorbent for removal of nickel from aqueous solutions- Kinetics and Equilibrium studies. The studies reveals that the Sisal fibre can be considered to be a cheap and viable adsorbent for the removal of nickel from aqueous solution.

[5] Vinod A.R et al., did a study on “Treatability studies of selective fibrous packing medias for sewage treatment”, which reveals that the coconut coir packing density 40kg/m³ showed higher removal efficiency of organic matter and nutrients in comparison to 70kg/m³. Cost effective and locally available medias such as coconut coir fibres, coffee husk can be used as an alternative option for sewage treatment.

[6] Bharati Sunil et al., did a study on “Coconut coir: A media to treat the wastewater”, which reveals that naturally available low cost media proves essentially a best option to industrialists to prevent the environmental pollution. Coconut coir fibre is rich in cellulose and lignin, having a high specific area and wetting ability factor which are essential for bacterial adhesion in fixed film processes.



| Volume 10, Issue 3, May 2023 |

III. PROBLEMS STATEMENT

Water is one of the most important elements involved in the creation and development of healthy life. Since water is such a vital resource for survival of both plants and animals, it is our responsibility to manage this resource. Current and future fresh water demand could be met by enhancing water use efficiency and demand management. Thus wastewater or low quality water is emerging as potential source for demand management after essential treatment. The use of various fixed beds having higher surface area is effective in removing organic matter and nutrients from municipal wastewater. In present study efforts have been made to check the efficiency of two different fibrous material-coconut coir fibre and areca husk fibre at two different packing densities and two different heights as submerged aerated fixed film beds for treating domestic wastewater. The use of agricultural by products in wastewater treatment can necessarily reduce the cost of treatment plant.

IV. PROPOSED METHODOLOGY

In our present study we have checked the feasibility of Agave sisalana and Areca husk fibres as filter media for wastewater treatment. Wastewater quality analysis have been conducted in the laboratory for parameters such as BOD, COD, chlorides, nitrates, sulphates.

Agave sisalana, is a species of Agave native to southern Mexico but widely cultivated and naturalized in many other countries. It yields a stiff fibre used in making various products. The term sisal may refer either to the plant's common name or the fibre, depending on the context. It is sometimes referred to as "sisal hemp", because for centuries hemp was a major source for fibre, and other fibre sources were named after it. The sisal fibre is traditionally used for rope and twine, and has many other uses, including paper, cloth, footwear, hats, bags, carpets, and dartboards.

Sisal plants, Agave sisalana, consist of a rosette of sword-shaped leaves about 1.5–2 metres (4.9–6.6 ft) tall. Young leaves may have a few minute teeth along their margins, but lose them as they mature. The sisal plant has a 7–10 year life-span and typically produces 200– 250 commercially usable leaves. Each leaf contains an average of around 1000 fibres. The fibres account for only about 4% of the plant by weight. Sisal is considered a plant of the tropics and subtropics, since production benefits from temperatures above 25 degrees Celsius and sunshine.

Fibre is extracted by a process known as decortication, where leaves are crushed and beaten by a rotating wheel set with blunt knives, so that only fibres remain. The production is typically on large scale, the leaves are transported to a central decortication plant, where water is used to wash away the waste parts of the leaf. The fibre is then dried, brushed and baled for export. Proper drying is important as fibre quality depends largely on moisture content. Artificial drying has been found to result in generally better grades of fibre than sun drying, but is not always feasible in the developing countries where sisal is produced. Fibre is subsequently cleaned by brushing. Dry fibres are machine combed and sorted into various grades, largely on the basis of the previous in-field separation of leaves into size groups.

Sampling:

Grab samples was collected in plastic cans rinsed with distilled water. Sample was collected from open drainage channels. Samples were analysed for following parameters i.e BOD, COD, chloride, sulphate, nitrate, pH, turbidity.

V. CONCLUSION

Instead of conventional media such as plastic, textiles etc use of natural fibrous materials as fixed bed in wastewater treatment equally shows promising removal efficiency of organics and nutrients. The spent fibre are rich in nutrients and can be used as organic manure.

VI. ACKNOWLEDGMENTS

The authors would like to express an acknowledgement to the Faculty of Civil Engineering Department and management of Swaminarayan Siddhanta Institute Of Technology, Nagpur, Maharashtra, India, for providing the facilities to accomplish this study. The author also wishes to acknowledge cooperation given by laboratory technician from Faculty of Civil Engineering Swaminarayan Siddhanta Institute Of Technology, Nagpur, Maharashtra, to complete this study.



REFERENCES

1. A R Vinod , R M Mahalingegowda (2012), Studies on Natural Fibrous Materials as Submerged Aerated Beds for Wastewater Treatment, Elixir International Journal
2. Bharati Sunil Shete, N P Shinkar (2014), Fixed Film Fixed Bed Reactor- Low Cost Approach, International Journal of Civil Structural Environmental and Infrastructure Engineering Research and Development (IJCSEIERD), Volume 4, Issues 4
3. Bharati Sunil Shete, D R Narendra P Shinkar (2015), Coconut Coir: A Media to Treat the Wastewater, IJPRET, Volume 3
4. Manoj Prabhakar , Sudipto Sarkar , Laxmi Narayan Sethi, Avinash Kunmar (2015), Ammonia Removal from Aquaculture Wastewater Using Coconut Coir Media in Lab Scale Batch Reactors , Journal Of Energy Research And Environmental Technology (JERET), Volume 2 No 1
5. Mrs. Bharati Sunil Shete, Dr. Narendra P. Shinkar ,research scholar; SGBAU, Amravati Dr. Sau. Kamaltai Gawai Institute of Engineering & Technology, Darapur, Amravati, Maharashtra, Lecturer department of Civil Engineering, Government Polytechnic, Gadge Nagar, Amravati, “ Coconut coir: a media to treat the wastewater”, international journal of pure and applied research in engineering and technology , Bharati Sunil Shete, IJPRET, 2015; volume 3 (9): 91-97.
6. Mahalingegowda. R.M and Vinod. A.R, dept of environmental engineering, PES College of Engineering, Mandya, Karnataka, “Studies on natural fibrous materials as submerged aerated beds for wastewater treatment, Vinod A.R et al./Elixir Pollution 51(2012) 10759- 10762.
7. Kudaligama K V V S , Thurul W M, Yapa P A J., “Effect of Bio-brush medium: a coir fibre based biomass retainer on treatment efficiency of an anaerobic filter type reactor”, Journal of the Rubber Research Institute of Sri Lanka.(2015) 87,15-22



INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



International Journal of Advanced Research in Arts, Science, Engineering & Management (IJARASEM)

| Mobile No: +91-9940572462 | Whatsapp: +91-9940572462 | ijarase@gmail.com |

www.ijarase.com